

Pleated Sediment JUMBO filter cartridge



2 High

1 High



Pleated filter cartridges are designed for high flow and / or low pressure applications in light sediment areas. Very suitable for rainwater tanks. Pleated cartridges do not provide the same contaminant removal performance of standard 'depth' type filter cartridges.

Specifications

- Micron rating: 5, 10, 20 micron (nominal)
- Materials of construction: Food Grade polypropylene and media
- Temperature range: 4 – 40°C (not for use in hot water)
- Duty: PL for reduction of sediment, turbidity, particles
- Flow rate: <30 lpm 1 high | <50 lpm 2 high
- Filter cartridge change: 12 months max
- Length: 254mm or 508mm
- Diameter: 110mm

Features & Benefits

- High surface area – low pressure drop and high flow rates
- Range of porosities to suit application
- Individually wrapped, sealed and labelled
- Pure polypropylene construction - food grade
- Competitive value product

Application

- Domestic Whole House System
- Commercial high flow
- Light industrial
- Chemical - check compatibility
- Prefiltration
- Sea water

CODE	REECE CODE	MICRON	HIGH	LENGTH	WIDTH
PL5W	1911273	5	1	254mm	114mm
PL10W	1911265	10	1	254mm	114mm
PL20W	1911518	20	1	254mm	114mm
PL5W20	1911274	5	2	508mm	114mm
PL10W20	1911266	10	2	508mm	114mm
PL20W20	1911519	20	2	508mm	114mm