

# Cabinet Coolers

## Punchbowl

### P Series



#### Features

- Suitable for all the common HFC and HCFC refrigerants including R22, R134a & R404A/R507
- Efficient inner grooved copper tubing with corrosion protected lacquer coating on return bends
- Balanced acrylic fans with ball bearing race motors
- Suitable for capillary or TX valve operation
- Epoxy coated fins

### PDC Series – Dual Coil – Medium Temperature

Cat. No.	Model No.	Cap. Watts @ 6 KTD			No. of Fans	Motor Input Watts	Connections mm		Overall Dimensions mm		
		R404A	R134a	R22			Suction	Liquid	Length	Width	Height
2710416	PDC45	455	428	450	1	35	9.5	9.5	565	335	160
2710417	PDC60	606	570	600	1	35	9.5	9.5	565	335	160
2710418	PDC80	808	760	800	1	35	9.5	9.5	565	335	160
2710419	PDC100	1010	950	1000	1	35	9.5	9.5	610	430	160
2710415	PDC120*	1212	1140	1200	1	35	12.7	12.7	610	430	160
2710435	PDC160*	1616	1520	1600	1	35	12.7	12.7	610	430	200
2710436	PDC185*	1869	1757	1850	1	35	12.7	12.7	610	430	200

\*Fitted with 6.35mm External Equaliser

Ratings based on -4°C SST for medium temperature models and -24°C SST on low temperature models.

