

Induced Draft Evaporators



Cabero

CH – Water Defrost Evaporators 500mm Fans

Product Code	Model	Capacity @ -4°C SST & 6 KTD Watts – MID POINT						
		R404A	R452A	R448A	R449A	R134a	R450A	R513A
	CH4C1/50W-1	8626	8232	8407	8320	7969	7794	8057
	CH4D1/50W-1	10160	9680	9886	9783	9371	9165	9474
	CH4E1/50W-1	11454	10838	11069	10953	10492	10262	10608
	CH4G1/50W-1	13424	12515	12782	12648	12116	11850	12249
3509010	CH4C2/50W-1	17252	16464	16815	16639	15939	15588	16114
3509011	CH4D2/50W-1	20319	19360	19772	19566	18743	18331	18949
3509012	CH4E2/50W-1	22908	21676	22137	21907	20984	20523	21215
3509013	CH4G2/50W-1	26848	25031	25563	25297	24232	23699	24498
3509014	CH4D3/50W-1	30479	29041	29659	29350	28114	27496	28423
3509015	CH4E3/50W-1	34362	32514	33206	32860	31477	30785	31823
3509016	CH4G3/50W-1	40272	37546	38345	37945	36348	35549	36747
3509017	CH4D4/50W-1	40638	38721	39545	39133	37485	36661	37897
3509018	CH4E4/50W-1	45816	43352	44275	43814	41969	41046	42430
3509019	CH4G4/50W-1	53696	50061	51126	50594	48463	47398	48996

Capacities based on EN328 Midpoint ratings SC2: Air inlet temp 2°C, Evaporating temp -4°C, 6K TD.