

# Suction Accumulators



## Emerson



Cat. No.	Part No.	Conn. ODF Solder	Capacity kW – Evaporating Temperature °C									Holding Capacity (kg) 50% of System Charge 4.4°C Liquid			Liquid Holding Capacity* kg	Weight kg
			R134a			R22			R404A, R507			R134a, R22	R404A, R507	R448A, R449A		
			-18	-7	5	-18	-7	5	-18	-7	5					
2710800	A-AS-384	1/2"	2.1	2.8	4.2	3.2	4.9	7	2.8	3.5	4.6	0.7	0.7	0.6	0.9	0.8
2710801	A-AS-3125	5/8"	2.8	4.2	6	4.9	7.4	10.5	4.2	5.6	7.0	1.4	1.1	1.3	1.4	1.0
2710802	A-AS-3126	3/4"	3.5	5.6	8.1	6.3	9.8	14.0	5.3	7.0	9.0	1.4	1.1	1.3	1.4	1.0
2710803	A-AS-596	3/4"	2.4	5.6	8.1	6.3	9.8	14.0	5.3	7.0	9.0	2.7	2.4	2.5	2.7	2.4
2710804	A-AS-597	7/8"	6.3	9.8	14	11.6	18.0	25.7	9.5	12.7	16.2	2.7	2.4	2.5	2.7	2.4
2710805	A-AS-5126	3/4"	3.5	5.6	8.1	6.3	9.8	14.0	5.3	7.0	9.0	3.6	3.4	3.3	4.0	3.6
2710806	A-AS--5127	7/8"	6.3	9.8	14	11.6	18.0	25.7	9.5	12.7	16.2	3.6	3.4	3.3	4.0	3.6
2710807	A-AS-5137	7/8"	3.7	9.8	14	11.6	18.0	25.7	9.5	12.7	16.2	3.8	3.6	3.6	4.3	3.7
2710808	A-AS-5139	1 1/8"	10.9	17.6	25.3	18.6	29.2	41.5	15.5	20.7	26.7	3.8	3.6	3.6	4.3	3.7
2710809	A-AS-5179	1 1/8"	3.8	17.6	25.3	18.6	29.2	41.5	15.5	20.7	26.7	5.4	4.5	5.0	5.4	3.8
2710810	A-AS-51711	1 3/8"	16.2	25.7	37.6	29.9	46.4	66	25.3	33.8	43.0	5.4	4.5	5.0	5.4	3.8
2710811	A-AS-61411	1 3/8"	5.6	25.7	37.6	29.9	46.4	66	25.3	33.8	43.0	6.3	5.7	5.9	5.9	5.6
2710812	A-AS-62013	1 5/8"	25.7	41.0	60.0	45.0	70.0	100.0	37.6	50.0	64.0	9.3	8.3	8.6	9.0	7.4