


THIRD ANGLE PROJECTION.

Q.R. No.		8047		CUSTOMER NO.		-		
CUSTOMER		LOVELOCK LUKE						
MOTOR RATING	VOLTS	415	Hz	50	Ph	3	Duty	A.O.M.
	RPM.	940			1.1			AMPS
	NOM. OUTPUT	375 WATTS						
ROTATION		CLOCKWISE AT DRIVE END (REVERSIBLE)						
CAPACITOR	START	-----	µF/V	RUN	-----			µF/V
ENCLOSURE		TOTALLY ENCLOSED						
MOTOR TYPE		3 PHASE		INSULATION CLASS		B130		
THERMAL PROTECTION		AUTO RESET OVERLOAD						
APPLICATION		FAN.VERTICAL,SHAFT-UP						
BEARING D.E.		6204 DDU			LUBRICATION		LONG LIFE, WIDE RANGE	
BEARING N.D.E.		6204 DDU						
SUPPLY LEAD		FLEX 2500±30 WITH CONDUIT ENTRY						
EARTH PROVISION		VIA SUPPLY LEAD						
BASIC BUILD SPECIFICATION		470-071-02			PAINT/ COLOUR		PC GREY PLAIN E/SHIELDS	
PERFORMANCE SPECIFICATION		SP94120-01						
CONNECTION DIAGRAM		393-135			RATING LABEL		SSTDAUTO.FMT	



SPECIAL REQUIREMENTS:

- 1)_WEATHERPROOF MOTORS TO SPEC ES050.
- 2)_DRAIN PLUGS (ARROW CLIP) FITTED ON D.E. ENDSHIELD ONLY.
- 3)_ WASHER FIBRE TO BE FITTED ON TIE RODS BOTH SIDES.

MOTOR WEIGHT	10.1 kg.	
DRAWN	Muntana	09/11/2018
CHECKED	Pipat	16/11/2018
RELEASED	Suksakorn	16/11/2018
SCALE	N.T.S.	

FRAME	MOTOR	
STATUS		
R	B120:9436T-375-HCH:LGL	
SHEET	DWG. NO.	REVISION
A3	809436NTB-B11	L