

**195B0027** **FR**

Refrigerant: R134a, Segment usage: Refrigeration HT; Refrigeration LT;  
Refrigeration MT, Compressor power supply [V/Ph/Hz]: 220/1/50 220/1/60

**PRODUCT DETAILS**

<b>Gross weight</b>	11.34 kg
<b>Net weight</b>	11.34 kg
<b>EAN</b>	5702428583718
<b>Application energy level</b>	Universal
<b>Applications</b>	HBP LBP MBP
<b>Auxiliary winding resistance (start winding) for single-phase compressors alt [Ohm]</b>	11.9 Ohm
<b>Base plate type</b>	Universal
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Black
<b>Compressor power supply [V/Ph/Hz]</b>	220/1/50 220/1/60
<b>Configuration code</b>	Single
<b>Cut in current HST [A]</b>	10.9 A
<b>Cut in current LST [A]</b>	15.1 A
<b>Description</b>	FR10G
<b>Discharge connection angle [°]</b>	25 °
<b>Discharge connection comments</b>	Al-cap
<b>Discharge connection diameter [mm]</b>	6.2 mm
<b>Discharge connection material</b>	Cu-plated steel
<b>Economizer</b>	No
<b>Free gas volume [cm<sup>3</sup>]</b>	1350 cm <sup>3</sup>
<b>Frequency [Hz]</b>	50/60
<b>Height from baseplate [mm]</b>	191 mm
<b>High value of nominal voltage at 50Hz [V]</b>	240 V
<b>High value of nominal voltage at 60Hz [V]</b>	240 V
<b>High value of voltage range at 50Hz [V]</b>	255 V
<b>High value of voltage range at 60Hz [V]</b>	255 V
<b>Length [mm]</b>	243 mm
<b>Liquid injection</b>	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## PRODUCT DETAILS

Low value of nominal voltage at 50Hz [V]	220 V
Low value of nominal voltage at 60Hz [V]	220 V
Low value of voltage range at 50Hz [V]	187 V
Low value of voltage range at 60Hz [V]	187 V
LRA HST 60Hz [A]	10.9 A
LRA HST [A]	10.9 A
LRA LST [A]	10.5 A
Main winding resistance for single-phase compressors [Ohm]	7.1 Ohm
Model number	FR10G
Motor type	CSIR RSIR
No. of phases (compressor)	1
Oil quantity [cm <sup>3</sup> ]	450 cm <sup>3</sup>
Oil type	POE
Packing format	Single pack
Packing quantity	1
Phase	1
Process connection angle [°]	30 °
Process connection comments	Al-cap
Process connection diameter [mm]	6.2 mm
Process connection material	Cu-plated steel
Refrigerant	R134a
Refrigerant charge [kg] [Max]	0.9 kg
RLA	2.20 A
Rotational speed at 50Hz [rpm]	3000 rpm
Rotational speed at 60Hz [rpm]	3600 rpm
Segment usage	Refrigeration LT Refrigeration MT Refrigeration HT
Start capacitor capacitance	80 µF
Suction connection angle [°]	30 °
Suction connection comments	Al-cap
Suction connection diameter [mm]	8.2 mm
Suction connection material	Cu-plated steel
Swept volume [cm <sup>3</sup> ]	9.05 cm <sup>3</sup>
Technology	Reciprocating
Total height [mm]	196 mm
Type	FR
Type designation	Compressor
Voltage 50Hz [V]	220 V
Voltage 50Hz [V] [Max]	240 V
Voltage 60Hz [V]	220 V
Voltage 60Hz [V] [Max]	240 V
Width [mm]	156 mm
Winding temperature short term [°C] [Max]	135 °C

---

**PRODUCT DETAILS**

---

<b>Winding temperature stat [°C]</b>	125 °C
<b>[Max]</b>	

---

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

---

**Accessories****103G6880** [↗](#)**FR**

Refrigerant: R134a, Segment usage: Refrigeration HT; Refrigeration LT; Refrigeration MT, Compressor power supply [V/Ph/Hz]: 220/1/50 220/1/60

**117U6010** [↗](#)**Starting Relay FR**

Starting Relay FR

Image  
coming  
soon**117U5015** [↗](#)**Start capacitor**

START CAPACITOR 80µF, 220V - FR,NL

Image  
coming  
soon**103N2010** [↗](#)**Accessory**

COVER TL,NL,FR-220V

**118-1917** [↗](#)**MOUNTING ACCESSORIES**

MOUNTING ACCESSORIES

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.