



Example image

## CHARACTERISTICS

- UV-resistant

## TECHNICAL DATA

Product material

PE-HD

Thermal expansion

0.17 mm/(m·K)

Art. no.	Reece no.	DN	d, ø mm	di, ø mm	s mm	L m	A <sup>2</sup> cm <sup>2</sup>	PN bar	S
360.000.16.0	1430000	40	40	34	3	5	9	8.1	12.5
361.000.16.0	1430002	50	50	44	3	5	15.2	6.4	12.5
363.000.16.0	1430004	56	56	50	3	5	19.6	5.7	12.5
364.000.16.0	1430006	60	63	57	3	5	25.4	5	12.5
365.000.16.0	1430008	70	75	69	3	5	37.3	4.1	12.5
366.000.16.0	1430010	90	90	83	3.5	5	54.1	4	12.5
367.000.16.0	1430012	100	110	101.4	4.3	5	80.7	4	12.5

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d<sub>1</sub> ø mm</i>	<i>d<sub>2</sub> ø mm</i>	<i>s mm</i>	<i>L m</i>	<i>A<sup>2</sup> cm<sup>2</sup></i>	<i>PN bar</i>	<i>S</i>
<b>368.000.16.0</b>	1430014	125	125	115.2	4.9	5	104.5	4	12.5
<b>369.000.16.0</b>	1430016	150	160	147.6	6.2	5	171.1	4	12.5
<b>370.000.16.0</b>	1430018	200	200	187.6	6.2	5	276.4	3.2	16
<b>371.000.16.0</b>	1430020	250	250	234.4	7.8	5	431.5	3.2	16
<b>372.000.16.0</b>	1430022	300	315	295.4	9.8	5	685.3	3.2	16