



Mizu Bloc MK2 Floor Mount Bath Outlet Chrome

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Screw brass water inlet plate (10) to pre-installed male-threaded water supply in floor (ensure that adequate threaded male nipple is protruding through finished floor)

NOTE: For tiled floors, it is recommended that the floor be tiled to the lip of the water inlet plate (10). Installing the water inlet plate through tiles could increase the risk of damage to tiles.

2. Fix brass plate to floor via the 3 fixing slots:
 - 3 x concrete floor anchors for installation into a slab floor
 - 3 x timber bolts for installation into a timber floor

NOTE: Ensure that bolts are fixed to an area of adequate structural integrity

3. Slide cover plate (7) over spout (4)
4. Connect spout (4) to base plate (10) by sliding spout over 6mm connection with triple o-ring seal (9)
5. Fix spout to base via 2 pan-head screws (5)
6. Slide cover plate (7) down spout to conceal brass base
7. Operate outlet to check for leaks
8. It is recommended that a bead of flexible sealant be used in order to provide a seal between the chrome floor cover and finished floor surface

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions

Plumbers, please ensure a copy of the Installation Instructions are left with the end user for future reference