

**NEW**

# ROAIRVAC R32 1.5

Two stage vacuum pump



**+ Versatile**

Suitable for refrigerant classes A1, A2L and A2

**+ Strong**

Four-pole motor with high torque

**+ Compact**

Light and small housing for easy and ergonomic transport

**NEW**

# ROAIRVAC R32 1.5



**Gas ballast valve**

Reduction of water vapour in the oil container, guarantees higher evacuation power and service life

**Special filter**

Reduces oil mist on exhaust vent

**Light and high-quality casing**

Protects the integrated components

**Ergonomic handle**

Light, compact and easy to transport

**Removable cable**

Prevents cable damage

**Integrated vacuum gauge**

Simple and fast control of the evacuation process

**Integrated solenoid valve**

Prevents backwash of oil into the refrigeration system

**Four-pole motor**

Increased torque and high lifetime



Removable cable and power button for convenient starting procedure



Special filter for reducing oil mist on exhaust vent





Ergonomic handle for easy transport

**Technical Data**

Power	190W
Final vacuum	15 micron
Inlet	1/4"
Oil capacity	250ml
Refrigerant classes	A1, A2L, A2

**Accessories**

	
Mineral oil, 1 litre (No. 169200)	Set of 3 pressure hoses (No. 1500000030)

**Description**



10.1

**No.**

1000002399

Includes removable power cable and 600 ml mineral oil