

# MILLI GLANCE BASIN SET

## INSTALLATION INSTRUCTIONS

### Important Note

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS  
BASIN SET  
IN0276 REV A

**1**

- Measure centre distance between holes in basin top and cut the T-Piece to required length.
- Remove Handle, Handle Washer, Flange, Dress Plate, Top Locknut and one Washer.
- Fit Nuts and Plastic Olives to each end of the T-Piece, connect to the Tap Bodies and fasten Nuts.

**2**

- Push Assembly up through the holes in the Basin Top.
- Fasten both Tap Bodies using the Locknuts.

**PLEASE NOTE**  
Adjust the Top and Bottom Locknuts to ensure the Red Fibre Washer sits at a maximum of 6mm above the Basin Top, as shown:

MAX 6mm

**3**

- Place the Dress Plates over each of the Tap Bodies
- Firmly screw on the Flanges to secure the Dress Plates.
- Ensure that both Taps are in the closed position.
- Fit the Handle Washer around the Flange.
- Fit Handles onto the Tap Bodies.
- Fasten the Grub Screws using the Allen Key provided.

**4**

- Fit O-Ring to the groove on the base of the Spout.
- Push Spout onto T-Piece.
- Firmly fasten Spout Locknut.
- Connect to water supply
- Test and Check for leaks

recommended working pressure  
**150-500KPa**  
maximum hot water temperature  
**75 degrees**

**NOTE:**  
- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.  
- Flush out all pipe work prior to installation.  
- If the water temperature exceeds 75°C, an approved tempering valve must be fitted.  
- Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.  
Showers may not be suitable for use with:  
• Gravity-fed water systems  
• Some instantaneous hot water systems or

• Pressure supply less than 150kPa.  
NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.  
Failure to comply with the above may void all warranties.

**WARRANTY:**  
Please refer to the full warranty statement enclosed with the product before installing.

**MAINTENANCE AND CARE:**  
- Products should be cleaned with mild liquid detergent or soap and water.  
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.  
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

**DISCLAIMER:**  
While we aim to ensure the specifications shown are correct at the time of printing, we reserve the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

\*All measurements are shown in millimeters.

Plumbers, please ensure a copy of the installation instructions is left with the end user for future reference