

## Copper / Nylon Olives

### SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



### COPPER / NYLON OLIVE TEE

Product Number	Product Description
416065	NYLON OLIVE TEE 15C X 15C X 15C
413515	COPPER OLIVE TEE 20C X 20C X 15C
416060	NYLON OLIVE TEE 20C X 20C X 15C
416070	NYLON OLIVE TEE 20C X 20C X 20C
416080	NYLON OLIVE TEE 15C X 15C X 15FI



### COPPER / NYLON OLIVE STOP END

Product Number	Product Description
413570	COPPER OLIVE STOP END 20C
416085	NYLON OLIVE STOP END 15C



### NYLON OLIVE

Product Number	Product Description
605900	NYLON OLIVE 15MM (PKT100)
605904	NYLON OLIVE 20MM



### KINCO NUT

Product Number	Product Description
606900	KINCO NUT - BRASS 15MM
606905	KINCO NUT - BRASS 20MM
606910	KINCO NUT - C/P 15MM



**Disclaimer:** Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

**Don't risk it, use a licensed plumber.™**

**WaterMark**  
AS 3688  
WMKA01972

**reece**

# BRASSWARE

## Specification Sheet

### Copper / Nylon Olives

SPECIFICATIONS	
Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



NYLON OLIVE UNION	
Product Number	Product Description
415995	NYLON OLIVE UNION 15C X 15C
416000	NYLON OLIVE UNION 20C X 20C
416010	NYLON OLIVE UNION 15C X 10C
416015	NYLON OLIVE UNION 20C X 15C



COPPER / NYLON OLIVE UNION (FEMALE)	
Product Number	Product Description
416045	NYLON OLIVE UNION 15FI X 15C
416050	NYLON OLIVE UNION 20FI X 20C
416055	NYLON OLIVE UNION 20FI X 15C
413175	COPPER OLIVE UNION 20FI X 15C



NYLON OLIVE UNION (MALE)	
Product Number	Product Description
415990	NYLON OLIVE ELBOW 20MI X 20C
416020	NYLON OLIVE UNION 15MI X 15C
416025	NYLON OLIVE UNION 20MI X 20C
416035	NYLON OLIVE UNION 20MI X 15C
416040	NYLON OLIVE UNION 15MI X 20C



NYLON OLIVE ELBOW	
Product Number	Product Description
415930	NYLON OLIVE ELBOW 15C X 15C
415935	NYLON OLIVE ELBOW 20C X 20C
415936	NYLON OLIVE ELBOW 20C X 15C



**Disclaimer:** Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

**Don't risk it, use a licensed plumber.™**

**WaterMark**  
AS 3688  
WMKA01972

**reece**

## Copper / Nylon Olives

## SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



## NYLON OLIVE ELBOW (FEMALE)

Product Number	Product Description
415960	NYLON OLIVE ELBOW 15FI X 15C
415965	NYLON OLIVE ELBOW 20FI X 20C
415975	NYLON OLIVE ELBOW 15FI X 15C LUGGED
415980	NYLON OLIVE ELBOW 20FI X 20C LUGGED



## NYLON OLIVE ELBOW (MALE)

Product Number	Product Description
415945	NYLON OLIVE ELBOW 15MI X 15C
415955	NYLON OLIVE ELBOW 20MI X 15C



## NYLON OLIVE LUGGED ELBOW (MALE)

Product Number	Product Description
415950	NYLON OLIVE ELBOW 15MI X 15C LUGGED



**Disclaimer:** Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

**Don't risk it, use a licensed plumber.™**

**WaterMark**  
AS 3688  
WMKA01972

**reece**