

American Standard EasySet Preset

SPECIFICATIONS

Recommended Use	Domestic, Hotel & Commercial	
Colour	Chrome	
Recommended Pressure Range	150 - 500kPa	
Max Continuous Working Pressure	500kPa	
Max Continuous Working Temperature	50°C	
Suitable for Storage Tank Hot Water	Yes	
Suitable for Continuous Flow Hot Water	Yes	
Suitable for Gravity Feed Hot Water	No	
Hot and Cold water inlet pressure should be equal		
WARRANTY		



WARRANI	r

Ø46

Places refer to Marronty Page for full Terms and Conditions		
Spare Parts & Labour	12 Months	
Warranty - Domestic Use	10 Years	

rG 1/2"

93

G 1/2"


Î

Î

Please refer to Warranty Page for full Terms and Conditions

64~72

119 13.5







ree

Dimensions are nominal measurements only.

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to varue specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

To see the complete American Standard range go to www.reece.com.au/bathrooms

Published 10/07/2018