

Caroma®

Cameo

Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Toilet Suite

Designed with the patented Orbital®
50mm Variable Offset Connector


CI/SfB	(74.1)	g3
Date	May 2015	

Supersedes all previous issues

3.24.2



S trap suite pictured





A close-coupled suite with smooth round corners and a concealed trap for ease of cleaning. The suite is supplied with the Caroma Orbital® connector, a patented 50mm variable offset connector for increased flexibility on setout. The **Cameo** cistern is an integrated system with a high performance outlet valve, fitted with low profile push buttons and is available in a 1/2" B.S.P. back entry option which completely conceals the inlet stop valve and connections for optimum installation appearance.

Pan: **Cameo** 4.5 litre full flush washdown pan with open flushing rim. Features the Caroma Orbital® 50mm variable offset connector.

Traps: S and P trap unvented.

Cisterns: **Cameo** cistern – has a free fitting lid and is suitable for domestic and light commercial applications.

Vandal Resistant Conversion Kit – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.

Inlet Valve and Overflow: **Standard Bottom Inlet Cistern** – available as right hand inlet which is interchangeable and incorporates the Apollo inlet valve. Internal overflow only.

Back Entry Cistern – An optional back entry conversion kit is available to convert the cistern from right hand bottom inlet to concealed back entry. Code No.687254.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.

Fixing: The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.

Seats: The **Profile** seat is provided as standard with the Cameo suite in both soft close or standard hinge options.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

