

Packaged Condensing Units

COMPAC Compac

Hermetic Reciprocating Series

Low Temperature Applications – R404A/R448A/R452A



Condensing Units

Product Code	Model Number	Ambient Temp. °C	Capacity Watts											
			Evaporating Temperature °C											
			R404A				R448A				R452A			
			-30	-25	-20	-15	-30	-25	-20	-15	-30	-25	-20	-15
3508139	PACS2480Z-EVO-XC	30	1945	2524	3175	3902	1712	2295	2968	3734	1863	2435	3089	3828
		32	1864	2430	3066	3773	1638	2208	2865	3614	1785	2344	2982	3702
		38	1616	2142	2729	3379	1416	1946	2557	3253	1544	2063	2652	3316
		43	1403	1895	2441	3042	1230	1728	2301	2954	1338	1822	2370	2985
3508140	PAC2480Z-EVO-XG	30	1929	2471	3074	3737	1687	2234	2857	3558	1829	2367	2972	3649
		32	1846	2376	2965	3612	1612	2147	2757	3444	1749	2275	2867	3529
		38	1598	2093	2639	3239	1394	1894	2465	3110	1509	1999	2551	3166
		43	1393	1858	2370	2929	1218	1691	2232	2843	1311	1771	2288	2865
3508141	PACS2511Z-EVO-XC	30	2532	3280	4125	5067	2232	2990	3869	4875	2411	3155	4008	4973
		32	2426	3157	3981	4900	2135	2876	3737	4722	2307	3034	3867	4810
		38	2102	2781	3544	4394	1846	2538	3344	4269	1990	2665	3438	4313
		43	1829	2464	3176	3967	1611	2262	3023	3899	1724	2355	3076	3894
3508142	PAC2511Z-EVO-XG	30	2541	3315	4194	5174	2236	3016	3925	4965	2415	3182	4066	5067
		32	2423	3173	4026	4979	2129	2886	3771	4786	2301	3045	3903	4877
		38	2082	2763	3538	4406	1826	2518	3331	4271	1970	2645	3427	4318
		43	1814	2437	3148	3945	1596	2234	2991	3869	1710	2328	3046	3868
3508035	PAC2513Z	30	2946	3981	5178	6536	2609	3641	4868	6293	2806	3828	5028	6408
		32	2787	3789	4948	6263	2465	3464	4653	6038	2651	3641	4803	6141
		38	2322	3225	4270	5458	2047	2948	4029	5295	2197	3089	4137	5349
		43	1948	2770	3721	4804	1718	2542	3535	4705	1834	2643	3598	4705
3508036	PAC2516Z	30	3424	4556	5850	7299	3035	4170	5501	7030	3290	4413	5709	7176
		32	3259	4356	5608	7011	2884	3983	5275	6761	3122	4210	5465	6887
		38	2770	3759	4887	6151	2442	3437	4612	5969	2628	3611	4746	6032
		43	2371	3270	4294	5442	2092	3001	4080	5332	2227	3124	4159	5334
3508037	PAC2522Z	30	4571	5974	7598	9446	4024	5439	7117	9069	4349	5739	7372	9256
		32	4371	5730	7302	9092	3841	5213	6841	8740	4153	5501	7083	8911
		38	3780	5009	6429	8049	3310	4557	6044	7787	3576	4794	6227	7887
		43	3301	4423	5719	7199	2892	4041	5416	7034	3107	4220	5530	7051
3508038	PAC2525Z	30	5014	6477	8134	9985	4410	5891	7610	9573	4769	6221	7889	9780
		32	4804	6227	7837	9634	4219	5660	7335	9249	4564	5977	7599	9436
		38	4178	5480	6947	8583	3660	4985	6527	8296	3953	5245	6726	8405
		43	3664	4863	6211	7711	3216	4445	5880	7529	3452	4641	6003	7548

Capacities based on EN13215 Midpoint ratings: Return Vapour 20°C, Subcooling 3K.