

HOTRUN X6



To be connected to single-phase power supply

Dimensions	315 x 204 x 130 mm	
Power	2.5/3.5/4.6/6.0 kWatt	
Voltage	1x240 Volts	
Current	10/16 / 20 / 25 Amp	
IP rating	IP24	
Connection	1/2 BSP"	
Weight	4 kg	
Performance (at $\Delta T = 25^\circ C$)	Set to 2.8kW	Flowrate 1.5 L/min
	Set to 3.8kW	Flowrate 2.0 L/min
	Set to 4.8kW	Flowrate 2.5 L/min
	Set to 6.0kW	Flowrate 3.2 L/min
Response time	< 10 seconds	
Pressure rating	Max 2MPa	

Variable programmable power rating to be set at 2.5, 3.5, 4.6 or 6 kWatt

Variable programmable temperature limiter can be set&locked to any required temperature limits between 25°C and 60°C

Variable temperature setting by the end user (below limiter temperature)

Tip: Allow 50mm on sides for cord etc and 100mm top and bottom for water connections to allow the cover to be opened after installation

Tip: Base your model selection on the winter inlet water temperature

Tip: Position within 6 metres of outlet if possible to minimise legionella risk



Features

1. Pressure resistant up to 3MPa (leak free guarantee for 8 years)
2. Variable power supply selection (kW)
3. Remote life time monitoring and diagnostics for fault conditions
4. Highly energy efficient and will only use exact amount of power required
5. Remote temperature control
6. Built in temperature limiter
7. Size of an A4 piece of paper
8. Digital temperature control and display
9. 10 year leak-free warranty, 2 years on all other parts, option for extended warranty years