

caroma®

Caravelle 2000


Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

3.25.1



Caravelle 2000

Vitreous China 4.5/3 litre Dual Flush Close-Coupled Toilet Suite



A close-coupled suite with smooth round corners and a concealed trap for ease of cleaning, the **Caravelle 2000** matched suite uses Caroma Smartflush technology to deliver the latest water-saving technology in sanitaryware products. The **Caravelle 2000** close-coupled vitreous china toilet suite delivers a 4.5/3 litre dual flush. The Caravelle 2000 cistern is an integrated system comprising of cistern with high performance outlet valve, fitted with low profile push buttons and is available in a 1/2" B.S.P. back inlet option which completely conceals the inlet stop valve and connections for optimum installation appearance. For an update on Smartflush refer to www.smartinnovation.com.au

- Pan:** **Caravelle 2000 Smartflush** 4.5 litre full flush washdown pan with open flushing rim. Optional 40mm Offset Connector available.
- Traps:** S or P-trap unvented.
- Cisterns:** **Caravelle 2000 Smartflush Cistern** – has a free fitting lid and is suitable for domestic and light commercial applications.
Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.
- Inlet Valve and Overflow:** **Standard Bottom Entry Cistern** – available as right hand inlet which is interchangeable and incorporates new Quietflow 2 inlet valve. Internal overflow only.
Optional Back Entry Cistern – is fitted with a Unifil inlet valve as standard. Available in internal and septic external overflow versions.
Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.
- Fixing:** The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.
- Seats:** The following Caroma seats are recommended: **Pedigree, Pedigree II, Scandinavia, Pressalit 2000, Caravelle 2000, Avalon, Trident** or **Deluxe**. The **Caravelle 2000** seat is supplied as standard with bottom inlet. See sheet 5.01 SEATS for further details.
- Colours:** White and Ivory.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

