

Flared Compression

SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



FLARED COMPRESSION UNION (MALE)

Product Number	Product Description
602575	COMP UNION FLARED 6MI X 15C
602610	COMP UNION FLARED 10MI X 10C
602620	COMP UNION FLARED 10MI X 15C
602660	COMP UNION FLARED 15MI X 10C
602670	COMP UNION FLARED 15MI X 15C
602675	COMP UNION FLARED 15MI X 15C C/P
602680	COMP UNION FLARED 15MI X 20C
602705	COMP UNION FLARED 20MI X 15C
602715	COMP UNION FLARED 20MI X 20C
602725	COMP UNION FLARED 20MI X 25C
602755	COMP UNION FLARED 25MI X 20C
602765	COMP UNION FLARED 25MI X 25C
602775	COMP UNION FLARED 25MI X 32C
602810	COMP UNION FLARED 32MI X 32C
602860	COMP UNION FLARED 40MI X 40C
602910	COMP UNION FLARED 50MI X 50C
602955	COMP UNION FLARED 65MI X 65C
603000	COMP UNION FLARED 80MI X 80C



FLARED COMPRESSION ELBOW

Product Number	Product Description
605250	COMP ELBOW FLARED 15C X 15C
605300	COMP ELBOW FLARED 20C X 20C
605350	COMP ELBOW FLARED 25C X 25C
605415	COMP ELBOW FLARED 20C X 15C RED



Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

Don't risk it, use a licensed plumber.™

WaterMark
AS 3688
WMKA01972

reece

Flared Compression

SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



FLARED COMPRESSION UNION (MALE)

Product Number	Product Description
604050	COMP UNION FLARED 6FI X 6C
604160	COMP UNION FLARED 15FI X 10C
604170	COMP UNION FLARED 15FI X 15C
604180	COMP UNION FLARED 15FI X 20C
604205	COMP UNION FLARED 20FI X 15C
603075	COMP UNION FLARED 20C X 15C RED
604215	COMP UNION FLARED 20FI X 20C
604265	COMP UNION FLARED 25FI X 25C
604310	COMP UNION FLARED 32FI X 32C
604355	COMP UNION FLARED 40FI X 40C
604410	COMP UNION FLARED 50FI X 50C
604600	COMP UNION FLARED 15C X 15C
604650	COMP UNION FLARED 20C X 20C
604700	COMP UNION FLARED 25C X 25C
604720	COMP UNION FLARED 50C X C



FLARED COMPRESSION ELBOW (MALE)

Product Number	Product Description
603665	COMP ELBOW FLARED 15MI X 15C
603675	COMP ELBOW FLARED 15MI X 20C
603705	COMP ELBOW FLARED 20MI X 15C
603715	COMP ELBOW FLARED 20MI X 20C
603750	COMP ELBOW FLARED 25MI X 20C
603755	COMP ELBOW FLARED 25MI X 25C
603800	COMP ELBOW FLARED 32MI X 32C
603805	COMP ELBOW FLARED 40MI X 40C
603810	COMP ELBOW FLARED 50MI X 50C



Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

Don't risk it, use a licensed plumber.™

WaterMark
AS 3688
WMKA01972

reece

Flared Compression

SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



FLARED COMPRESSION TEE

Product Number	Product Description
606020	COMP FLARED TEE TUT 15C
606030	COMP FLARED TEE TUT 20C
606300	COMP FLARED TEE TUT 20C X 15C X 15C RED
606310	COMP FLARED TEE TUT 20C X 15C X 20C RED
606320	COMP FLARED TEE TUT 20C X 20C X 15C RED



FLARED COMPRESSION TEE (FEMALE)

Product Number	Product Description
606400	COMP FLARED TEE DUT 15C X 15C X 15FI
606460	COMP FLARED TEE DUT 20C X 20C X 15FI
606470	COMP FLARED TEE DUT 20C X 20C X 20FI
606510	COMP FLARED TEE DUT 15FI X 15C X 15C



COMPRESSION NUT

Product Number	Product Description
606800	CROX NUTS 15MM BRASS (FLAT SEAT)
606805	CROX NUTS 15MM C/P (FLAT SEAT)
605625	COMP NUT FLARED 15C
605630	COMP NUT FLARED 15C C/P
605635	COMP NUT FLARED 20C



FLARED COMPRESSION CONE

Product Number	Product Description
605820	COMP CONE FLARED 15C BRASS OLIVE
605835	COMP CONE FLARED 20C BRASS OLIVE



Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

Don't risk it, use a licensed plumber.™

WaterMark
AS 3688
WMKA01972

reece

Flared Compression

SPECIFICATIONS

Maximum Operating Pressure	1400kPa
Maximum Operating Temperature	95°C
Material	DR (Dezincification Brass)
Standards	AS 3688 - Water supply and gas systems - Metallic fittings and end connections
Watermarked Certification	WMKA01972
Surface Finish	Brass Finish or Chrome Plated



FLARED COMPRESSION ELBOW (FEMALE)

Product Number	Product Description
605065	COMP ELBOW FLARED 15FI X 15C
605070	COMP ELBOW FLARED 15FI X 15C C/P
605075	COMP ELBOW FLARED 15FI X 20C
605105	COMP ELBOW FLARED 20FI X 15C
605115	COMP ELBOW FLARED 20FI X 20C
605155	COMP ELBOW FLARED 25FI X 25C
605160	COMP ELBOW FLARED 32FI X 32C
605165	COMP ELBOW FLARED 40FI X 40C
605175	COMP ELBOW FLARED 50FI X 50C



FLARED COMPRESSION LUGGED ELBOW

Product Number	Product Description
605450	COMP ELBOW FLARED 15FI X 15C LUGGED
605455	COMP ELBOW FLARED 15FI X 15C LUGGED CP
605460	COMP ELBOW FLARED 15FI X 20C LUGGED
605470	COMP ELBOW FLARED 20FI X 20C LUGGED
605500	COMP ELBOW 15C X 15MI NIPPLE LUGGED



Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12/12/2019

Don't risk it, use a licensed plumber.™

WaterMark
AS 3688
WMKA01972

reece