



COOL-FIT PE Plus Codo 45°, d32-d225

Model:

- Aislamiento PE100 **SDR17** métrico
- Aislamiento: PUR
- Chaqueta exterior resistente al impacto Color: negro
- Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing

d/D (mm)	PN (bar)	Part No.	weight (kg)	D1 (mm)	L (mm)	L1 (mm)	z (mm)	closest inch (inch)	Type
32/90	16	738 153 108	0.108	97	72	36	11	1	A
40/110	16	738 153 109	0.162	117	76	40	11	1 ¼	A
50/110	16	738 153 110	0.218	117	82	44	13	1 ½	A
63/125	16	738 153 111	0.315	132	89	48	16	2	A
75/140	16	738 153 112	0.650	147	98	55	18	2 ½	A
90/160	16	738 153 113	1.030	168	117	62	30	3	A
110/180	16	738 153 114	1.270	188	138	72	41	4	A
160/250	16	738 153 117	4.100	258	161	90	46	6	A
225/315	16	738 153 120	17.603	324	278	110	143	8	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>