


THIRD ANGLE PROJECTION.


# **MOTOR SPECIFICATION**

#### 8061S137-80 6680 CUSTOMER NO. Q.R. No. **CUSTOMER VARIOUS** 240 **AOM 50 VOLTS** Hz Ph Duty MOTOR MAX. INPUT 910 2.3 **AMPS RATING 250 WATTS** NOM. OUTPUT **CLOCKWISE AT DRIVE END ROTATION** CAPACITOR START μF/V RUN 4/440 $\mu F/V$ **ENCLOSURE TOTALLY ENCLOSED CSR** INSULATION CLASS **B130** MOTOR TYPE **AUTO RESET THERMAL OVERLOAD** THERMAL PROTECTION **FAN - SHAFT HORIZONTAL APPLICATION** BEARING D.E. 6202 DDU C3 LONG LIFE, LUBRICATION **WIDE RANGE** BEARING N.D.E. 6202 DDU C3 SUPPLY LEAD IN TERM. BOX **EARTH PROVISION** BASIC BUILD 305-570-05 **SPECIFICATION PC GREY CASE** PAINT/ **COLOUR PLAIN E/SH** PERFORMANCE SP85115-01 **SPECIFICATION** CONNECTION **RATING** 393-333-01 **SSTDAUTO.FMT**



LABEL

## FINAL INSPECTED MOTORS MUST COMPLY WITH ELECTRIC MOTOR VIBRATION SPECIFICATION (ES049)



- 87.0 -

### SPECIAL REQUIREMENTS:

DIAGRAM

- 1) WEATHERPROOF MOTORS TO ES050
- 2) NON DRIVER E/SH TO BE ASSEMBLED SO THAT LEAD EXIT HOLE IS CLOSED TO THE WELD
- 3) WASHER FIBRE TO BE FITTED ON TIE RODS BOTH SIDES.

UNL	LSS OTHER	NISE SPE	CIFIED	
ı	DIMENSIONS ARE IN MM.			
	TOLERANCES			
DE	CIMALS	AN	GULAR	
.X	± 1.0	±	30'	

THIS DRAWING REMAINS THE PROPERTY OF FASCO

MOTORS AND MAY NOT BE USED, COPIED OR ISSUED WITHOUT WRITTEN PERMISSION FROM FASCO MOTORS

± 0.1

			kg
	DRAWN	Veeranut	07/11/2018
	CHECKED	Pipat	08/11/2018
	RELEASED	Suksakorn	08/11/2018
S	SCALE	N.T.S.	

7.6

MOTOR WEIGHT



29/7-8 MOO 3, BANGKRUAY - SAINOI Rd., BANGKRANG, MUANG NONTHABURI DISTRICT. NONTHABURI 11000 THAILAND

FRAME	MOTOR
STATUS R	B115:8556T-250-XCD
SHEET	DWG NO

8061S137-80

REVISION

U