



# Bridgland Tape



**9507249**  
Bridgland Petrolatum Tape  
100mm x 10mtr



**9507250**  
Bridgland Petrolatum Tape  
150mm x 10mtr

SPECIFICATIONS		
Thickness	Test Method: Value:	ASTM D1000 1.15mm (average)
Weight	Test Method: Value:	ASTM D751 1.44 kg/m <sup>2</sup> (average)
Breaking Strength	Test Method: Value:	ASTM D1000 ≥ 4.0 N/mm
Elongation at Break	Test Method: Value:	ASTM D1000 10% (average)
Water Vapour Transmission	Test Method: Value:	ASTM E96 0.006 perms avg.
Resistance to Cathodic Disbondment	Test Method: Value:	ASTM G8, A (30 days) 180mm <sup>2</sup> avg.
Resistance to Acids, Alkalies, and Salts	Value:	Excellent
Maximum Temperature	Value:	+55°C
Product Packaging: 9507249	Width: Length: Carton Qty:	100mm 10m 12 rolls
Product Packaging: 9507250	Width: Length: Carton Qty:	150mm 10m 8 rolls

## Product Description

Bridgland Tape is based upon a non-woven polyester fabric, which has been fully impregnated and saturated with a petrolatum compound and blended with inert fillers.

## Product Characteristics

- Bridgland Tape exhibits wide ranging resistance to acids, alkalis, and salts.
- Bridgland Tape exhibits non-hardening and non-cracking properties, which allow the product to accommodate both substrate vibration and movement. Will adhere and remain attached to clean, wet, or dry metal surfaces.

## Product Uses

**Pipeline:** Corrosion protection of above ground, below ground pipes and metal fittings.

**Other:** Tie rods, starter bars, bond breaker, slip form release tape, roof sheet isolation tape.

**Disclaimer:** Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12.10.2020

