



Example image

CHARACTERISTICS

- Can be welded with Geberit electrofusion tools
- UV-resistant

TECHNICAL DATA

Installation temperature	-10 – +40 °C
Product material	PE-HD

Art. no.	Reece no.	DN	d, ø mm	D cm	E cm	H cm	X cm
These articles are suitable for the following system: Geberit PE							
360.771.16.1	1430420	40	40	5.2	2.8	6	0.3
361.771.16.1	1430421	50	50	6.2	2.8	6	0.3
363.771.16.1	1430422	56	56	6.8	2.8	6	0.3
364.771.16.1	1430423	60	63	7.6	2.8	6	0.3
365.771.16.1	1430424	70	75	8.9	2.8	6	0.3

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d_e mm</i>	<i>D cm</i>	<i>E cm</i>	<i>H cm</i>	<i>X cm</i>
366.771.16.1	1430425	90	90	10.4	2.8	6	0.3
367.771.16.2	1430426	100	110	12.5	2.8	6	0.3
368.771.16.1	1430429	125	125	14.2	2.8	6	0.3
369.771.16.1	1430427	150	160	17.8	2.8	6	0.3
These articles are suitable for the following system: Geberit Silent-db20							
363.771.16.1	1430422	56	56	6.8	2.8	6	0.3
364.771.16.1	1430423	60	63	7.6	2.8	6	0.3
365.771.16.1	1430424	70	75	8.9	2.8	6	0.3
366.771.16.1	1430425	90	90	10.4	2.8	6	0.3
367.771.16.2	1430426	100	110	12.5	2.8	6	0.3
369.771.16.1	1430427	150	160	17.8	2.8	6	0.3