

Scala Top Mount Hob Mixer

INSTALLATION GUIDE

Tapware is to be installed by a Licenced Plumber in accordance with AS/NZS 3500:2003

**Recommended working water pressure 300-500kpa.
Maximum water temperature is 65 deg.C.**

Mounting Surface Requirements

- Mixer clearance hole in mounting surface is to be between 40-45mm.
- Bench thickness 12-50mm

Progressive Hob Mixer

- Remove ext. nut and mixer clamp from mixer body and fit dress ring.
- Attach hot and cold flexible hoses as marked on mixer body. Also attach the "Out Mixed Water" flexible hose to the position marked 'OUT'.
- Lower the mixer on to the mounting surface.
- NOTE: The "FRONT" engraved on mixer body must be positioned facing the operator.
- Working from the underside, fit mixer clamp and fix the mixer using the ext. nut (tighten well).
- Connect the flexible hoses to hot and cold lines.
- Connect "out" mixed water flexible hose to Outlet/ Spout.
- After mixer is secured and connections are made, check function and inspect for any leaks.

Plumbers Note

- On-site high pressure line testing must be conducted with the Mixer in the closed position. (STATIC TEST ONLY).
- Under no circumstances is the Mixer to be opened when exceeding the maximum stated water pressure.
- At the completion of the testing, do not relieve any high pressure by opening the Mixer.
- Exposing the internals of the Mixer Cartridge to higher than specified water pressures, will void the manufacturer's warranty.

