

**003Z8203** [↗](#)**AB-QM, DN 20, With test plugs, External Thread**

AB-QM DN 20, with test plugs, External thread, PN25, pressure independent balancing and control valve

**PRODUCT DETAILS**

|  |   |
|--|---|
| <b>Gross weight</b>                      | 0.77 kg   |
| <b>Net weight</b>                        | 0.69 kg   |
| <b>EAN</b>                               | 5714279039320   |
| <b>Actuator connection</b>               | M30 x 1.5   |
| <b>Connection types</b>                  | External Thread   |
| <b>Description</b>                       | AB-QM DN 20, with test plugs, External thread, PN25, pressure independent balancing and control valve |
| <b>Differential pressure [kPa] [Max]</b> | 600 kPa   |
| <b>Flow nominal [m<sup>3</sup>/h]</b>    | 1.1 m <sup>3</sup> /h   |
| <b>Media temperature [°C] [Max]</b>      | 95 °C   |
| <b>Media temperature [°C] [Min]</b>      | -10 °C  |
| <b>Pressure class</b>                    | PN 25   |
| <b>Product group</b>                     | Pressure independent balancing and control valves   |
| <b>Starting pressure [kPa]</b>           | 16 kPa  |
| <b>Stroke [mm]</b>                       | 4 mm  |
| <b>Test plugs</b>                        | With test plugs   |
| <b>Type</b>                              | AB-QM   |
| <b>Valve body material</b>               | DZR Brass (CW 602N)   |
| <b>Valve size</b>                        | DN 20   |

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)