



## COOL-FIT 4.0 T90° reduced, d32-d225

### Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- \*Available as long as stocks last

d/D (mm)	d1/D1 (mm)	PN (bar)	Code	Weight (kg)	
75/140	63/125	16	<b>738 203 218</b>	0.863	
90/160	63/125	16	<b>738 203 222</b>	1.232	
90/160	75/140	16	<b>738 203 223</b>	1.293	
110/180	63/125	16	<b>738 203 227</b>	1.972	
110/180	75/140	16	<b>738 203 228</b>	1.949	
110/180	90/160	16	<b>738 203 229</b>	2.037	
*	160/250	63/125	16	<b>738 203 247</b>	5.150
*	160/250	90/160	16	<b>738 203 249</b>	5.147
*	160/250	110/180	16	<b>738 203 250</b>	5.220
	160/250	140/200	16	<b>738 204 251</b>	5.540
	225/315	63/125	16	<b>738 203 264</b>	16.832
	225/315	90/160	16	<b>738 203 266</b>	16.889
	225/315	110/180	16	<b>738 203 267</b>	16.805
	225/315	140/200	16	<b>738 204 268</b>	17.100
	225/315	160/250	16	<b>738 203 269</b>	18.500
	160/250	63/125	16	<b>738 203 447</b>	5.150
	160/250	90/160	16	<b>738 203 449</b>	5.147
	160/250	110/180	16	<b>738 203 450</b>	5.220

d/D (mm)	d1/D1 (mm)	D2 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	z1 (mm)	Closest inch (inch)	Type
75/140	63/125	147	116	55	48	36	228	2 ½	A
90/160	63/125	168	130	62	48	43	253	3 - 2	A
90/160	75/140	168	130	62	55	43	252	3 - 2 ½	A
110/180	63/125	188	154	72	48	57	267	4 - 2	A
110/180	75/140	188	154	72	55	57	268	4 - 2 ½	A
110/180	90/160	188	154	72	62	57	268	4 - 3	A
*	160/250	258	192	90	48	77	327	6 - 2	A
*	160/250	90/160	258	90	62	77	327	6 - 3	A
*	160/250	110/180	258	90	72	77	325	6 - 5	A
	160/250	140/200	258	90	84	77	340	6 - 5	A
	225/315	63/125	324	355	110	48	220	8 - 2	A
	225/315	90/160	324	355	110	62	220	8 - 3	A
	225/315	110/180	324	355	110	72	220	8 - 4	A
	225/315	140/200	324	335	110	84	220	8 - 5	A
	225/315	160/250	324	355	110	90	220	8 - 6	A
	160/250	63/125	258	192	90	48	77	6 - 1	
	160/250	90/160	258	192	90	62	77	6 - 3	
	160/250	110/180	258	192	90	72	77	6 - 5	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

# Data sheet

valid from: 4/14/20

---



e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>