



## COOL-FIT 4.0 Reducción, d250-d450

### Model:

- Aislamiento PE100 **SDR17** métrico
- Aislamiento hecho de GF espuma HE
- Chaqueta exterior resistente al impacto Color: negro
- Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- Tipo B: conexión de espiga con extremos pelados



d/D (mm)	d1/D1 (mm)	PN (bar)	Part No.	weight (kg)	D2 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	closest inch (inch)	Type
40/110	32/90	16	<b>738 903 206</b>	0.250	117	143	40	36	17	1 ¼ - 1	A
50/110	32/90	16	<b>738 903 209</b>	0.280	117	151	44	36	21	1 ½ - 1	A
50/110	40/110	16	<b>738 903 210</b>	0.320	117	149	44	40	15	1 ½ - 1 ¼	A
63/125	32/90	16	<b>738 903 212</b>	0.217	132	160	48	36	26	2 - 1	A
63/125	40/110	16	<b>738 903 213</b>	0.232	132	159	48	40	21	2 - 1 ¼	A
63/125	50/110	16	<b>738 903 214</b>	0.243	132	159	48	44	17	2 - 1 ½	A
75/140	63/125	16	<b>738 903 318</b>	0.264			55	48	170	2 ½ - 2	B
90/160	63/125	16	<b>738 903 322</b>	0.387			62	48	190	3 - 2	B
90/160	75/140	16	<b>738 903 323</b>	0.416			62	55	189	3 - 2 ½	B
110/180	63/125	16	<b>738 903 327</b>	0.566			72	48	204	4 - 2	B
110/180	75/140	16	<b>738 903 328</b>	0.577			72	55	205	4 - 2 ½	B
110/180	90/160	16	<b>738 903 329</b>	0.644			72	62	205	4 - 3	B
160/250	63/125	16	<b>738 903 347</b>	1.298			90	48	244	6 - 2	B
160/250	90/160	16	<b>738 903 349</b>	1.323			90	62	244	6 - 3	B
160/250	110/180	16	<b>738 903 350</b>	1.362			90	72	242	6 - 4	B
160/250	140/200	16	<b>738 904 351</b>	1.664			90	84	257	6 - 5	B
225/315	63/125	16	<b>738 903 364</b>	2.960			110	48	295	8 - 2	B
225/315	90/160	16	<b>738 903 366</b>	3.018			110	62	295	8 - 3	B
225/315	110/180	16	<b>738 903 367</b>	3.079			110	72	295	8 - 4	B
225/315	140/200	16	<b>738 904 368</b>	3.172			110	84	296	8 - 5	B
225/315	160/250	16	<b>738 903 369</b>	3.550			110	90	279	8 - 6	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>