

**SM110-4VI****Scroll compressor, SM110S4VC**

Refrigerant: R22, Segment usage: Air conditioning, Compressor power supply  
[V/Ph/Hz]: 400/3/50 460/3/60

**PRODUCT DETAILS**

<b>Gross weight</b>	78.71 kg
<b>Net weight</b>	73 kg
<b>EAN</b>	5702428839440
<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Scroll compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Brazed
<b>Description</b>	SM110-4
<b>Diameter [mm]</b>	254 mm
<b>Discharge connection height [mm]</b>	515 mm
<b>Discharge connection pipe size [in]</b>	7/8 in
<b>Discharge connection size [in]</b>	7/8 in
<b>Drawing number</b>	8552037b
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	33 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting standard</b>	ODF
<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	C
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 Nm
<b>GP LP torque [Nm]</b>	15 Nm
<b>High side max pressure (Ps)</b>	30.2 bar
<b>High Side TS Max</b>	150 °C
<b>High Side TS Min</b>	-35 °C
<b>High Side Volume</b>	1.1 L
<b>High value of nominal voltage at 50Hz [V]</b>	400 V
<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	440 V

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Scroll compressor, SM110S4VC

## PRODUCT DETAILS

High value of voltage range at 60Hz [V]	506 V
IP protection class	IP54 (with cable gland)
Low side max pressure (Ps)	25 bar
Low Side TS Max	63 °C
Low Side TS Min	-35 °C
Low Side Volume	13.6 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	342 V
Low value of voltage range at 60Hz [V]	414 V
LRA	130 A
Maximum Operating Current [MOC]	20 A
MCC	22 A
Model number	SM110S4VC
Motor protection	Internal overload protector
Mounting torque [Nm]	21 Nm
Nominal cooling capacity 60 kBTU/h	107.85 kBTU/h
Nominal cooling capacity at 50Hz	23.5 kW
Nominal cooling capacity at 60Hz	31.6 kW
Number of starts per hour [Max]	12
Oil charge [L]	3.25 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	48 Nm
Oil reference	160P
Oil type	Mineral
Packaging height [mm]	596 mm
Packaging length [mm]	470 mm
Packaging weight [Kg]	78 kg
Packaging width [mm]	370 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw 4.8 mm
Refrigerant	R22
Refrigerant charge [kg] [Max]	10 kg
Relief valve	None
RLA	15.7 A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Air conditioning
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	178 mm
Suction connection pipe size [in]	1 3/8 in

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Scroll compressor, SM110S4VC

## PRODUCT DETAILS

Suction connection size [in]	1 3/8 in
Swept volume [cm <sup>3</sup> ]	144.2 cm <sup>3</sup>
Technology	Scroll
Test dif [bar] [Max]	24 bar
Test HP [bar] [Max]	32 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	2 Nm
Torque power [Nm]	3 Nm
Total height [mm]	558 mm
Type	SM
Type designation	Compressor
Viscosity [cP]	32 cP
Winding resistance for three-phase compressors with identical windings [Ohm]	1.05 Ohm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

## Accessories



**8156138** [🔗](#)

**Mounting kit**

Mounting kit for one-scroll compressor, including 4 grommets, 4 sleeves, 4 bolts, 4 washers



**8156135** [🔗](#)

**Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp**

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp



**7750009** [🔗](#)

**Discharge thermostat kit**

Discharge thermostat kit



**8153003** [🔗](#)

**Adaptor**

Solder sleeve, P10 (1-3/4" rotolock, 1-3/8" ODF)



**8156132** [🔗](#)

**Gasket, 1-3/4"**

Gasket, 1-3/4"



**7755010** [🔗](#)

**Acoustic hood for scroll compressor S110-S120**

Acoustic hood for scroll compressor S110-S120

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**8156013** [🔗](#)

**Gasket set, 1-1/4", 1-3/4", 2-1/4", OSG gaskets black and white**

Gasket set, 1-1/4", 1-3/4", 2-1/4", OSG gaskets black and white



**120Z0405** [🔗](#)

**Adaptor**

Solder sleeve adaptor set (1-3/4" rotolock, 1-3/8" ODF), (1-1/4" rotolock, 7/8" ODF)



**8173230** [🔗](#)

**T block connector 52 x 57 mm**

T block connector 52 x 57 mm

Spare Parts



**7705006** [🔗](#)

**MCI**

Electronic soft start kit, MCI 15 C



**120Z0361** [🔗](#)

**Surface sump heater + bottom insulation, 48 W, 24 V, CE mark, UL**

Surface sump heater + bottom insulation, 48 W, 24 V, CE mark, UL



**7754001** [🔗](#)

**Mineral oil, 160P, 2-litre can**

Mineral oil, 160P, 2-litre can



**8156019** [🔗](#)

**Oil sight glass with gaskets (black and white)**

Oil sight glass with gaskets (black and white)



**120Z0381** [🔗](#)

**Surface sump heater + bottom insulation, 48 W, 400 V, CE mark, UL**

Surface sump heater + bottom insulation, 48 W, 400 V, CE mark, UL



**120Z0382** [🔗](#)

**Surface sump heater + bottom insulation, 48 W, 460 V, CE mark, UL**

Surface sump heater + bottom insulation, 48 W, 460 V, CE mark, UL

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Spare Parts

**8156129** [🔗](#)**Gasket for oil sight glass (white teflon)**

Gasket for oil sight glass (white teflon)

**120Z0466** [🔗](#)**Belt type crankcase heater, 65 W, 460 V, CE mark, UL**

Belt type crankcase heater, 65 W, 460 V, CE mark, UL

**8168022** [🔗](#)**Rotolock valve, V10 (1-3/4" rotolock, 1-3/8" ODF), Service kit**

VALVE SETS V10 1 3/4"-1 3/8"

**8168030** [🔗](#)**Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF), Service kit**

VALVE SETS V05 1 1/4"-7/8"

**120Z0039** [🔗](#)**Belt type crankcase heater, 65 W, 400 V, CE mark, UL**

Belt type crankcase heater, 65 W, 400 V, CE mark, UL

**7773117** [🔗](#)**Belt type crankcase heater, 65 W, 400 V, CE mark, UL**

Belt type crankcase heater, 65 W, 400 V, CE mark, UL

**120Z0380** [🔗](#)**Surface sump heater + bottom insulation, 48 W, 230 V, CE mark, UL**

Surface sump heater + bottom insulation, 48 W, 230 V, CE mark, UL

**7703392** [🔗](#)**Valve set**

Packing format: Multi pack, Packing quantity: 6

**7773107** [🔗](#)**Belt type crankcase heater, 65 W, 230 V, CE mark, UL**

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.