



Bridgland Multi Purpose Primer

SPECIFICATIONS	
Solid Content	> 98%
Specific Gravity	1.08
Specific Volume	925 cm ³ / kg
Cone Penetration at 25° C (ASTM D937)	160 ± 20 dmm (Average)
Flash Point	> 180° C
Coverage	2 to 5 m ² / kg
Application Temperature	-5 to +45° C
Service Temperature	-20 to +50° C
Maximum Temperature	55° C
Product Packaging	Weight: 2.5kg Carton Qty: 4/Carton



Product Description

Bridgland Primer Paste is a petrolatum based primer used in the preparation of metal surface prior to contouring with Bridgland Mastic or wrapping with Bridgland Tapes.

Product Characteristics

- Bridgland Primer Paste will fill imperfections and enable uniform adhesion of Bridgland Mastic and Bridgland Tape to cleaned substrate.
- Bridgland Primer Paste is formulated for stability and plasticity over a wide temperature range.
- Bridgland Primer exhibits non-hardening and non-cracking properties to accommodate vibration and movement of the substrate. Will adhere and remain attached to clean, wet or dry metal surfaces.
- Highly resistant to mineral acids, alkalis and salts.

Product Uses

Pipeline: Corrosion protection, water-proofing, sealing of pipelines, joints, fittings, cables and tensioning members when used as part of the Bridgland System.

Other: Rust prevention of screw threads, valve spindles, turnbuckles, wire rope etc. and temporary protection on exposed metals.

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12.10.2020

