

**195B0059** [↗](#)**Reciprocating compressor, SC18G**

This product is not available in this store. Please contact your local Customer Service Center.

**Customer Service Center** [↗](#)

Refrigerant: R134a, Segment usage: Refrigeration HT; Refrigeration LT;  
Refrigeration MT, Compressor power supply [V/Ph/Hz]: 220/1/50 220/1/60

**PRODUCT DETAILS**

<b>Gross weight</b>	14.3 kg
<b>Net weight</b>	14.3 kg
<b>EAN</b>	5702424535032
<b>Application energy level</b>	Universal
<b>Applications</b>	HBP LBP MBP
<b>Auxiliary winding resistance (start winding) for single-phase compressors alt [Ohm]</b>	13.7 Ohm
<b>Base plate type</b>	Universal
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Black
<b>Compressor power supply [V/Ph/Hz]</b>	220/1/50 220/1/60
<b>Configuration code</b>	Single
<b>Cut in current HST [A]</b>	20.4 A
<b>Description</b>	SC18G
<b>Discharge connection angle [°]</b>	37 °
<b>Discharge connection comments</b>	Rubber plug
<b>Discharge connection diameter [mm]</b>	6.2 mm
<b>Discharge connection height [mm]</b>	100 mm
<b>Discharge connection material</b>	Copper
<b>Economizer</b>	No
<b>Free gas volume [cm<sup>3</sup>]</b>	1460 cm <sup>3</sup>
<b>Frequency [Hz]</b>	50/60
<b>Height from baseplate [mm]</b>	203 mm
<b>High value of nominal voltage at 50Hz [V]</b>	240 V
<b>High value of nominal voltage at 60Hz [V]</b>	240 V
<b>High value of voltage range at 50Hz [V]</b>	255 V
<b>High value of voltage range at 60Hz [V]</b>	255 V
<b>Length [mm]</b>	255 mm
<b>Liquid injection</b>	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Reciprocating compressor, SC18G

## PRODUCT DETAILS

Low value of nominal voltage at 50Hz [V]	220 V
Low value of nominal voltage at 60Hz [V]	220 V
Low value of voltage range at 50Hz [V]	187 V
Low value of voltage range at 60Hz [V]	187 V
LRA HST 60Hz [A]	20.4 A
LRA HST [A]	20.4 A
Main winding resistance for single-phase compressors [Ohm]	3.7 Ohm
Model number	SC18G
Motor type	CSIR
No. of phases (compressor)	1
Nominal cooling capacity 60 kBTU/h	6.06 kBTU/h
Nominal cooling capacity at 60Hz	1.8 kW
Oil quantity [cm <sup>3</sup> ]	550 cm <sup>3</sup>
Oil type	POE
Packing format	Single pack
Packing quantity	1
Phase	1
Process connection angle [°]	37 °
Process connection comments	Rubber plug
Process connection diameter [mm]	6.2 mm
Process connection height [mm]	183 mm
Process connection material	Copper
Refrigerant	R134a
Refrigerant charge [kg] [Max]	1.3 kg
RLA	3.90 A
Rotational speed at 50Hz [rpm]	3000 rpm
Rotational speed at 60Hz [rpm]	3600 rpm
Segment usage	Refrigeration LT Refrigeration MT Refrigeration HT
Start capacitor capacitance	80 µF
Suction connection angle [°]	37 °
Suction connection comments	Rubber plug
Suction connection diameter [mm]	10.2 mm
Suction connection height [mm]	183 mm
Suction connection material	Copper
Swept volume [cm <sup>3</sup> ]	17.69 cm <sup>3</sup>
Technology	Reciprocating
Total height [mm]	209 mm
Type	SC
Type designation	Compressor
Voltage 50Hz [V]	220 V
Voltage 50Hz [V] [Max]	240 V
Voltage 60Hz [V]	220 V
Voltage 60Hz [V] [Max]	240 V
Width [mm]	151 mm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Reciprocating compressor, SC18G**

---

**PRODUCT DETAILS**

---

<b>Winding temperature short term</b> [°C] [Max]	135 °C
<b>Winding temperature stat [°C]</b> [Max]	125 °C

---

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)