



AB-QM, DN 32, With test plugs, External Thread

AB-QM DN 32, with test plugs, pressure independent balancing and control valve



PRODUCT DETAILS

Gross weight	2.3 kg
Net weight	2.3 kg
EAN	5710104029962
Actuator connection	M30 x 1.5
Connection types	External Thread
Description	AB-QM DN 32, with test plugs,
	pressure independent balancing and
	control valve
Differential pressure [kPa] [Max]	600 kPa
Flow nominal [m³/h]	3.2 m ³ /h
Media temperature [°C] [Max]	120 ℃
Media temperature [°C] [Min]	-10 °C
Pressure class	PN 16
Product group	Pressure independent balancing and
	control valves
Starting pressure [kPa]	25 kPa
Stroke [mm]	4.5 mm
Test plugs	With test plugs
Туре	AB-QM
Valve body material	DZR Brass (CW 602N)
Valve size	DN 32

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.